

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 3225-1296:102

Page 1 of 1

CATEGORY: Fire Dampers

LISTEE: Metal-Fab, P.O. Box 1138, Wichita, KS 67201
Contact: Jerold Jay (316) 943-4031

DESIGN: Models MFD, MFD3, MDFD, MDFD3, MFDUS and MFDUS3 curtain type fire dampers. Refer to listee's data sheet for detailed product description and operational considerations.

<i>Model</i>	<i>Max. Width</i>	<i>Max. Height</i>	<i>Max. Width</i>	<i>Max. Height</i>	<i>Position</i>
MDFD, MDFD3	36"	36"	NA	NA	Vertical
	36"	36"	80"	40"	Horizontal
MFD	60"	60"	120"	120"	Vertical
	40"	40"	80"	40"	Horizontal
MFD3	48"	48"	NA	NA	Vertical
	40"	40"	80"	40"	Horizontal
MFDUS, MFDUS3	48"	48"	NA	NA	Vertical
	40"	40"	80"	40"	Horizontal

RATING: 1-1/2 and 3 Hour

INSTALLATION: In accordance with the listee's printed installation instructions, applicable codes & ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, rating and UL label.

APPROVAL: Listed as 1-1/2 and 3 hour fire-rated for use in heating, ventilating and air conditioning duct system passing through fire resistive walls and partitions. Suitable for vertical and horizontal installations.

12-06-2000



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued:

JUNE 16, 2003

*Listing Expires **June 30, 2004***

Authorized By:

DIANE K. AREND, Senior Deputy
Program Manager